

VÁLVULAS INVERSORAS DE 4 VÍAS



*Referidas a : T^a evaporación= +7°C / T^a condensación= +54°C / Recalentamiento= 5,5K / Pérdida de carga= 2 Psi

Tipo	Conexiones		Potencias admisibles en KW				€/und	CODIGO
	Aspiración	Descarga	R22		R404A			
			Maxi	Mini	Maxi	Mini		
RV10AD141200S0	7/8"	3/4"	29,9	15,8	35,2	11,9	220,00	RV10AD141200S0
RV10AD181400S0	1 1/8"	7/8"	33,5	15,8	35,2	11,9	220,00	RV10AD181400S0
RV01AD08050000	1/2"	5/16"	3,5	1,4	4,9	1,8	Consultar	RV01AD08050000
RV02BD08060000	1/2"	3/8"	8,8	2,6	9,1	3,5		67,90
RV02DD10060000	5/8"	3/8"	8,8	2,6	9,1	3,5	67,90	RV02DD10060000
RV03ED12080000	3/4"	1/2"	10,55	3,5	11,4	3,9	90,50	RV03ED12080000
RV06AD14080000	7/8"	1/2"	19,3	3,5	20,1	3,9	139,00	RV06AD14080000
RV06AD14100000	7/8"	5/8"	19,3	3,5	20,1	3,9	139,00	RV06AD14100000

Tipo	Longitud cable	Voltaje	Consumo W	Color	€/und	CODIGO
LDK41480100	1200 mm	230 V 50/60 Hz	6 W	Verde	Consultar	LDK41480100
LDK31480100	1200 mm	110 V 50/60 Hz	6 W	Negro	Consultar	LDK31480100
LDK11480100	1200 mm	24 V 50/60 Hz	6 W	Rojo	Consultar	LDK11480100